1209 Country Club Rd, Indianapolis, IN 46234
https://www.uswatersystems.com
Need Help? 800-608-8792
connect@uswatersystems.com

Product Specifications

CARB-CAT
(NSF 42 & PROP 65)

SPECIFICATION		VALUE	TEST METHOD
Iodine Number	(mg/g)	Min: 1050	ASTM D4607
Apparent Density	(g/cc)	Min: 0.52	ASTM D2854
Moisture	(% by wt)	Max: 5	ASTM D2867
Total Ash	(% by wt)	Max: 3	ASTM D2866
Extractable pH		7-11	ASTM D3838
Catalytic Activity (Temp Increase)	(°C)	20	HC - LAB/STP/56
MCA removal capacity	(mg/g)	150	HC Method

PARTICLE SIZE 12x40 ASTM MESH				ASTM D2862
> 12 mesh	(1.70 mm)	(% by wt)	Max: 5	
12x40	(1.70mm x 0.425mm)	(% by wt)	Min: 90	
< 40 mesh	(0.425 mm)	(% by wt)	Max: 5	

CARBCAT™ PREMIUM CATALYTIC CARBON
Water Quality Association MEMBER
NSF
Do not use with water that is microbiologically unsafe or unknown quality without adequate disinfection before or after the system